

PI-400

PARAFFIN CONTROL/DEMULSIFIER

Wide range paraffin control/demulsifier

Description PI-400H is an effective paraffin solvent, paraffin inhibitor and demulsifier in one chemical package specifically designed for gas lift mandrel compatibility. It is effective on a wide range of crude oils. It prevents the formation of solid tank bottoms. It will help keep the crude in a liquid form during cold weather operations. PI-400 is most effective on dark paraffinic crudes.

Properties	Physical State:	Liquid	Specific Gravity:	0.75
	Freeze Point:	<0°F	Chemical Type	Polymer in Aromatic Solvent
	Boiling Point:	149-446°F	Color:	Clear
	Odor:	Hydrocarbon-like	Shelf Life:	1 Year

Application PI-400H is injected continuously at the wellhead or down the annulus via a side stream flush system for removal and inhibition of paraffin from downhole. Recommended treating rate is 100 to 2,000 ppm. Stimulation treatments may require 3 to 5 gallons of chemical per 1,000 gallons of fluid to be treated.

Compatibility PI-400H is incompatible with water in the container. There is no compatibility problem with produced water in the system.

Handling PI-400H is a flammable liquid. Keep away from heat, sparks, open flames and any ignition source. Refer to the Material Safety Data Sheet (MSDS) for handling and hazard data.

Packaging PI-400H is available in 55 gallon metal drums and metal totes.